

Алматы (7273)495-231	Ижевск (3412)26-03-58	Магнитогорск (4219)55-03-13	Пермь (342)205-81-47	Тверь (4352)63-31-42
Ангарск (3955)42-70-56	Иваново (4932)77-34-06	Москва (495)268-04-70	Ростов-на-Дону (863)308-18-15	Тольятти (8435)63-91-07
Архангельск (8182)63-90-72	Иркутск (395)279-98-46	Мурманск (8152)59-142-93	Рязань (4912)46-61-142	Томск (3835)98-41-53
Астрахань (8512)99-46-04	Казань (843)206-01-42	Набережные Челны (8552)20-53-41	Самара (846)206-03-16	Тула (4272)33-79-87
Барнаул (3852)73-04-42	Калининград (4012)72-03-81	Нижний Новгород (831)429-08-12	Саранск (8342)35-96-24	Тюмень (3452)66-21-18
Белгород (4735)40-23-142	Калуга (4242)92-23-67	Новокузнецк (3843)20-46-81	Санкт-Петербург (812)309-46-40	Улан-Удэ (3012)59-97-51
Благовещенск (4162)35-142-07	Кемерово (3842)65-04-62	Ноябрьск (3496)41-32-12	Саратов (845)249-38-78	Ульяновск (8435)24-23-59
Брянск (4232)59-03-52	Киров (8332)68-02-04	Новосибирск (383)357-86-73	Севастополь (8692)35-31-93	Уфа (347)359-42-12
Владивосток (423)249-42-31	Копомна (4966)23-41-49	Ноябрьск (3496)41-32-12	Симферополь (3652)67-13-56	Хабаровск (4212)92-98-04
Владикавказ (8672)42-90-42	Кострома (4942)77-07-42	Омск (3812)21-46-40	Смоленск (4212)29-41-42	Чебоксары (8435)42-53-07
Владимир (4935) 49-43-18	Краснодар (861)203-40-90	Орел (4262)44-53-42	Сочи (862)242-72-31	Челябинск (421)202-03-61
Волгоград (844)278-03-42	Красноярск (391)204-63-61	Оренбург (4232)37-68-04	Ставрополь (8652)20-65-13	Череповец (8202)49-02-142
Вологда (8172)26-41-59	Курск (4712)77-13-04	Пенза (8412)35-31-16	Сыктывкар (8212)42-95-17	Чита (3035)38-34-83
Воронеж (473)204-51-73	Курган (4352)50-90-47	Петрозаводск (8142)55-98-37	Сургут (3462)77-98-42	Якутск (4112)23-90-97
Екатеринбург (343)384-55-142	Липецк (4742)52-20-81	Псков (8112)59-10-37	Тамбов (4752)50-40-97	Ярославль (4422)69-52-93
Киргизия (996)312-96-26-47		Россия (495)268-04-70		Казахстан (772)734-952-31

<https://g-m.nt-rt.ru> || gfm@nt-rt.ru

Клеммные платы серии ТВ-D5008-АВВ.

Технические характеристики

Termination Board general characteristics:

Number of positions	Features
8	1) Power Supply voltage redundancy; 2) HART multiplexing; 3) Abnormal supply voltage signaling; 4) Cumulative module fault signaling.

Supported ABB S800 I/O Cards:

I/O Card Type	TU Type	I/O Card Model	Channels per I/O Card	TUs per board	Channels per board	Supported GM Modules(*)
Analog In	TU812	AI810, AI845	8	1	8	D5011S, D5014S, D5072S, D6011S, D6014S, D6072S
				2	16	D5011D, D5014D, D5072D, D6011D, D6014D, D6072D
	TU854	AI880A	8	1	8	D5011S, D5014S, D5072S, D6011S, D6014S, D6072S
				2	16	D5011D, D5014D, D5072D, D6011D, D6014D, D6072D

(*) Do not mix D5000 Intrinsically Safe barriers with D5000 Relay modules or D6000 isolators on same termination board.

Features:

- S800 AI Cards board interfaces.
- Termination Board for current signals: (0) 4 - 20 mA.
- 8 positions Termination Board for up to 16 channels.
- Lower cables installation and maintenance costs.
- Power supplies fault monitoring.
- Spare fuse provided.
- Mounting hardware provided for:
 - Wall mounting, M4 thread screw;
 - Wall mounting, M4 self tapping screw;
 - Single Din Rail mounting kit.

Ordering Information:

Model: TB-D5008-ABB-001

Technical Data:

Supply:
24 Vdc nom (20 to 30 Vdc) reverse polarity protected, double terminal blocks for redundant power supply, with OR diodes to mix supply voltages.
Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².
2 LEDs indication: green color, one for supply 1 and one for supply 2.
Protection fuse: 2 A time lag (spare fuse provided on Termination Board).


Fault detection:
1) Preventive - abnormal supply voltage: supply 1 or supply 2 is < 18 Vdc (Under Voltage, UV) or > 30 Vdc (Over Voltage, OV).
2) Critical - abnormal supply voltages or cumulative fault: both supplies are in under (< 18 Vdc) or over (> 30 Vdc) voltage condition OR cumulative fault indication (about presence of short or open field circuit for any DO channel).
LED fault signaling (for both case 1 and 2): 2 red LEDs (UV and OV of supply 1); 2 red LEDs (UV and OV of supply 2); a cumulative fault red LED.
Relay fault signaling (one for each case 1 or 2): a voltage free NE SPDT - 1 Form C relay contacts (de-energized in fault condition), with the following characteristics:
Contact material: AgCdO.
Contact rating: 2 A 36 Vac 72 VA, 2 A 48 Vdc 80 W (resistive load).
Mechanical / Electrical life: 30 * 10⁶ / 1 * 10⁵ operation, typical.
Coil status LED indication: yellow color, turn on when coil is energized.
Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

I/O card interface:
Connection: two 25 poles SUB-D male connectors (require female mating connectors).

HART Multiplexing:
Connection: 34 poles male connector (requires female mating connector).

Environmental conditions:
Operating: temperature limits – 40 to + 70 °C, relative humidity max 90 % non condensing, up to 35 °C.
Storage: temperature limits – 45 to + 80 °C.

Mounting:
Hardware included for mounting on wall and single DIN rail.
Weight: about 220 g (excluding modules and mounting options).
Location: Safe Area / Ordinary locations.
Dimensions: Width 147 mm, Depth 176 mm, Height 125 mm.





Loop Diagrams (TU812):


FIELD

SAFE AREA


Note : Do not mix D5000 Intrinsically Safe barriers with D5000 Relay modules or D6000 isolators on same termination board.



Loop Diagrams (TU854):



Termination Board Connections





Connections table to Interface Cards:

MODULE POSITION	MODULE CHANNEL NUMBER	INTERFACE CARD(S) CHANNEL NUMBER	MODULE CHANNEL POSITIVE (+) CONNECTION	MODULE CHANNEL NEGATIVE (-) CONNECTION	HART MULTIPLEXING CONNECTOR POSITIVE (+) PIN NUMBER	HART MULTIPLEXING CONNECTOR NEGATIVE (-) PIN NUMBER	NOTES
1	1A	1 on TU n.1	16 (CON1)	Gnd	1 (J9)	2 (J9)	<div>CON1, CON2:</div> <ul style="list-style-type: none">• Pole 13 is not connected.• +24 Vdc available on poles: 1, 14, 11, 24.• Ground available on poles: 2, 15, 12, 25. <div>J9:</div> <ul style="list-style-type: none">• Poles 33, 34 are not connected.
	1B	1 on TU n.2	16 (CON2)	Gnd	17 (J9)	18 (J9)	
2	2A	2 on TU n.1	17 (CON1)	Gnd	3 (J9)	4 (J9)	
	2B	2 on TU n.2	17 (CON2)	Gnd	19 (J9)	20 (J9)	
3	3A	3 on TU n.1	18 (CON1)	Gnd	5 (J9)	6 (J9)	
	3B	3 on TU n.2	18 (CON2)	Gnd	21 (J9)	22 (J9)	
4	4A	4 on TU n.1	19 (CON1)	Gnd	7 (J9)	8 (J9)	
	4B	4 on TU n.2	19 (CON2)	Gnd	23 (J9)	24 (J9)	
5	5A	5 on TU n.1	20 (CON1)	Gnd	9 (J9)	10 (J9)	
	5B	5 on TU n.2	20 (CON2)	Gnd	25 (J9)	26 (J9)	
6	6A	6 on TU n.1	21 (CON1)	Gnd	11 (J9)	12 (J9)	
	6B	6 on TU n.2	21 (CON2)	Gnd	27 (J9)	28 (J9)	
7	7A	7 on TU n.1	22 (CON1)	Gnd	13 (J9)	14 (J9)	
	7B	7 on TU n.2	22 (CON2)	Gnd	29 (J9)	30 (J9)	
8	8A	8 on TU n.1	23 (CON1)	Gnd	15 (J9)	16 (J9)	
	8B	8 on TU n.2	23 (CON2)	Gnd	31 (J9)	32 (J9)	

Termination Board description:


Note:
Relay contact is defined Normally Closed (NC) or Normally Open (NO) when RL1 or RL2 relays are de-energized (that is, coil status LED is turned off).
Relay is de-energized in fault status.

Power Supply redundancy:




LED Signaling:
Meaning of LEDs on termination boards:

TAG	LED COLOR	MEANING
Supply 1 On	GREEN	The LED is on when the Supply 1 is present, regardless of its voltage
Supply 1 Under V	RED	The LED is on when the Supply 1 is under-voltage (<18 V)
Supply 1 Over V	RED	The LED is on when the Supply 1 is over-voltage (>30 V)
Supply 2 On	GREEN	The LED is on when the Supply 2 is present, regardless of its voltage
Supply 2 Under V	RED	The LED is on when the Supply 2 is under-voltage (<18 V)
Supply 2 Over V	RED	The LED is on when the Supply 2 is over-voltage (>30 V)
Cumulative Fault	RED	The LED is on when at least one module/barrier reported a fault
Relay Power 1002 OK	YELLOW	The LED is on when both supply voltages are within the regular range (>18 V and <30 V)
Relay Fault	YELLOW	The LED is on when the following two conditions hold: 1. at least one voltage supply is within the regular range (>18 V and <30 V) 2. no module/barrier fault is reported





Relay Activation Conditions:
The two relays are activated according to the following rules:

TAG	ACTIVATION
1002 Power OK (RL1)	The relay is energized when both supply voltages are within the regular range (>18 V and <30 V), i.e. when "Relay 1002 Power OK" yellow LED is on.
Module Fault (RL2)	The relay is energized when the following two conditions hold: 1. at least one voltage supply is within the regular range (>18 V and <30 V) 2. no module/barrier fault is reported Therefore, the relay is energized when the "Fault" yellow LED is on.




DIN Rail mounting overall dimensions:





All dimensions are expressed in millimeters [inches]

Mounting features kit TB-OPT-001




Ref. Nr	Q.ty	Description	Material
1	2	T35 Din Rail Adapter	PA
2	6	3.5 x 9.5 Self tapping screw	Stainless Steel
3	6	M3 External Tooth lock Washer	Stainless Steel
4	6	M3 Washer	Stainless Steel
5	2	6 c 20 Spacer	PA

Wall mounting overall dimensions for M4 self tapping screw:





All dimensions are expressed in millimeters [inches]

Mounting features kit TB-OPT-001



Ref. Nr	Q.ty	Description	Material
6	4	M4 x 8 Screw	Stainless Steel
7	4	M4 External Tooth lock Washer	Stainless Steel
8	8	M4 Washer	Stainless Steel
9	4	Self Tapping Spacer	NI - Plated Brass


Wall mounting overall dimensions for M4 thread screw:



All dimensions are expressed in millimeters [inches]

Wall mounting features for M4 thread screw:

Mounting features kit TB-OPT-001



Ref. Nr	Q.ty	Description	Material
10	4	M4 x 8 Screw	Stainless Steel
11	8	M4 External Tooth lock Washer	Stainless Steel
12	8	M4 Washer	Stainless Steel
13	4	Threaded Spacer	NI - Plated Brass
14	4	M4 Nut	Stainless Steel

Characteristics:

General description:

This Termination Board (TB) provides direct connection between the I/O Card of the system and D5000 / D6000 Series modules.

The Intrinsically Safe protection and signal isolation between Safe and Hazardous Area, is provided by D5000 Series Associated Apparatus. The 24 Vdc Power Supply of the TB is connected to two plug-in terminal blocks, for a redundant power supply. The power supply for modules is given by TB power bus.

Termination Board general characteristics:

Number of positions	Features
8	1) Power Supply voltage redundancy; 2) HART multiplexing; 3) Abnormal supply voltage signaling; 4) Cumulative module fault signaling.

Supported ABB S800 I/O Cards:

I/O Card Type	TU Type	I/O Card Model	Channels per I/O Card	TUs Per board	Channels per board	Supported GM Modules*
Analog Out	TU812	AO810, AO845	8	1	8	D5020S, D6020S
				2	16	D5020D, D6020D
	TU852	AO845	8	1	8	D5020S, D6020S
				2	16	D5020D, D6020D

*Do not mix D5000 Intrinsically Safe barriers with D5000 Relay modules or D6000 isolators on same termination board.

Technical Data:

Supply:

24 Vdc nom (20 to 30 Vdc) reverse polarity protected, double terminal blocks for redundant power supply, with OR diodes to mix supply voltages.

Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

2 LEDs indication: green color, one for supply 1 and one for supply 2.

Protection fuse: 2 A time lag (spare fuse provided on Termination Board).

Fault detection:

1) Preventive - abnormal supply voltage: supply 1 or supply 2 is < 18 Vdc (Under Voltage, UV) or > 30 Vdc (Over Voltage, OV).

2) Critical - abnormal supply voltages or cumulative fault: both supplies are in under (< 18 Vdc) or over (> 30 Vdc) voltage condition OR cumulative fault indication (about presence of short or open field circuit for any DO channel).

LED fault signaling (for both case 1 and 2): 2 red LEDs (UV and OV of supply 1); 2 red LEDs (UV and OV of supply 2); a cumulative fault red LED.

Relay fault signaling (one for each case 1 or 2): a voltage free NE SPDT - 1 Form C relay contacts (de-energized in fault condition), with the following characteristics:

Contact material: AgCdO.

Contact rating: 2 A 36 Vac 72 VA, 2 A 48 Vdc 80 W (resistive load).

Mechanical / Electrical life: 30 * 10⁶ / 1 * 10⁵ operation, typical.

Coil status LED indication: yellow color, turn on when coil is energized.

Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

I/O card interface:

Connection: two 25 poles SUB-D male connectors (require female mating connectors).

HART Multiplexing:

Connection: 34 poles male connector (requires female mating connector).

Environmental conditions:

Operating: temperature limits – 40 to + 70 °C, relative humidity max 90 % non condensing, up to 35 °C.

Storage: temperature limits – 45 to + 80 °C.

Mounting:

Hardware included for mounting on wall and single DIN rail.

Weight: about 220 g (excluding modules and mounting options).

Location: Safe Area / Ordinary locations.

Dimensions: Width 147 mm, Depth 176 mm, Height 125 mm.


Features:

- S800 AO Cards board interfaces.
- 8 positions Termination Board for up to 16 channels.
- Lower cables installation and maintenance costs.
- Power supplies fault monitoring.
- Spare fuse provided.
- Mounting hardware provided for:
 - Wall mounting, M4 thread screw;
 - Wall mounting, M4 self tapping screw;
 - Single Din Rail mounting kit.

Ordering Information:

Model: TB-D5008-ABB-002

Image:



Termination Board 8 positions for ABB S800 (TU812) with Analog Input card AI810 (voltage signals)

Characteristics:

General description:

This Termination Board (TB) provides direct connection between the I/O Card of the system and D5000 / D6000 Series modules.
The Intrinsically Safe protection and signal isolation between Safe and Hazardous Area, is provided by D5000 Series Associated Apparatus. The 24 Vdc Power Supply of the TB is connected to two plug-in terminal blocks, for a redundant power supply.
The power supply for modules is given by TB power bus.

Termination Board general characteristics:

Number of positions	Features
8	1) Power Supply voltage redundancy; 2) HART multiplexing; 3) Abnormal supply voltage signaling; 4) Cumulative module fault signaling; 5) TB Voltage Output signals.

Supported ABB S800 I/O Cards:

I/O Card Type	TU Type	I/O Card Model	Channels per I/O Card	TUs Per board	Channels per board	Supported GM Modules(*)(**)
Analog In	TU812	AI810	8	1	8	D5011S, D5014S, D5072S, D6011S, D6014S, D6072S
				2	16	D5011D, D5014D, D5072D, D6011D, D6014D, D6072D

(*) Do not mix D5000 Intrinsically Safe barriers with D5000 Relay modules or D6000 isolators on same termination board.

(**) All modules must be configured as current source output.

Technical Data:

Supply:

24 Vdc nom (20 to 30 Vdc) reverse polarity protected, double terminal blocks for redundant power supply, with OR diodes to mix supply voltages.

Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

2 LEDs indication: green color, one for supply 1 and one for supply 2.

Protection fuse: 2 A time lag (spare fuse provided on Termination Board).

Fault detection:

1) Preventive - abnormal supply voltage: supply 1 or supply 2 is < 18 Vdc (Under Voltage, UV) or > 30 Vdc (Over Voltage, OV).

2) Critical - abnormal supply voltages or cumulative fault: both supplies are in under (< 18 Vdc) or over (> 30 Vdc) voltage condition OR cumulative fault indication (about presence of short or open field circuit for any DO channel).

LED fault signaling (for both case 1 and 2): 2 red LEDs (UV and OV of supply 1); 2 red LEDs (UV and OV of supply 2); a cumulative fault red LED.

Relay fault signaling (one for each case 1 or 2): a voltage free NE SPDT - 1 Form C relay contacts (de-energized in fault condition), with the following characteristics:

Contact material: AgCdO.

Contact rating: 2 A 36 Vac 72 VA, 2 A 48 Vdc 80 W (resistive load).

Mechanical / Electrical life: 30 * 10⁶ / 1 * 10⁵ operation, typical.

Coil status LED indication: yellow color, turn on when coil is energized.

Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

I/O card interface:

Connection: two 25 poles SUB-D male connectors (require female mating connectors).

HART Multiplexing:

Connection: 34 poles male connector (requires female mating connector).

Environmental conditions:

Operating: temperature limits – 40 to + 70 °C, relative humidity max 90 % non condensing, up to 35 °C.

Storage: temperature limits – 45 to + 80 °C.

Mounting:

Hardware included for mounting on wall and single DIN rail.

Weight: about 220 g (excluding modules and mounting options).

Location: Safe Area / Ordinary locations.

Dimensions: Width 147 mm, Depth 176 mm, Height 125 mm.


Features:

- S800 AI Cards board interfaces.
- Termination Board for voltage signals: (0) 2 - 10 V.
- 8 positions Termination Board for up to 16 channels.
- Lower cables installation and maintenance costs.
- Power supplies fault monitoring.
- Spare fuse provided.
- Mounting hardware provided for:
 - Wall mounting, M4 thread screw;
 - Wall mounting, M4 self tapping screw;
 - Single Din Rail mounting kit.

Ordering Information:

Model: TB-D5008-ABB-003

Image:



Characteristics:

General description:

This Termination Board (TB) provides direct connection between the I/O Card of the system and D5000 / D6000 Series modules.
The Intrinsically Safe protection and signal isolation between Safe and Hazardous Area, is provided by D5000 Series Associated Apparatus. The 24 Vdc Power Supply of the TB is connected to two plug-in terminal blocks, for a redundant power supply.
The power supply for modules is given by TB power bus.

Termination Board general characteristics:

Number of positions	Features
8	1) Power Supply voltage redundancy; 2) HART multiplexing; 3) Abnormal supply voltage signaling; 4) Cumulative module fault signaling; 5) TB Voltage Output signals.

Supported ABB S800 I/O Cards:

I/O Card Type	TU Type	I/O Card Model	Channels per I/O Card	TUs Per board	Channels per board	Supported GM Modules(*)
Analog In	TU812	AI845	8	1	8	D5011S, D5014S, D5072S, D6011S, D6014S, D6072S
				2	16	D5011D, D5014D, D5072D, D6011D, D6014D, D6072D

(*) Do not mix D5000 Intrinsically Safe barriers with D5000 Relay modules or D6000 isolators on same termination board.

Features:

- S800 AI Cards board interfaces.
- Termination Board for voltage signals: (0) 1 - 5 V.
- 8 positions Termination Board for up to 16 channels.
- Lower cables installation and maintenance costs.
- Power supplies fault monitoring.
- Spare fuse provided.
- Mounting hardware provided for:
 - Wall mounting, M4 thread screw;
 - Wall mounting, M4 self tapping screw;
 - Single Din Rail mounting kit.

Ordering Information:

Model: TB-D5008-ABB-004

Technical Data:

Supply:

24 Vdc nom (20 to 30 Vdc) reverse polarity protected, double terminal blocks for redundant power supply, with OR diodes to mix supply voltages.

Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

2 LEDs indication: green color, one for supply 1 and one for supply 2.

Protection fuse: 2 A time lag (spare fuse provided on Termination Board).

Fault detection:

1) **Preventive - abnormal supply voltage:** supply 1 or supply 2 is < 18 Vdc (Under Voltage, UV) or > 30 Vdc (Over Voltage, OV).

2) **Critical - abnormal supply voltages or cumulative fault:** both supplies are in under (< 18 Vdc) or over (> 30 Vdc) voltage condition OR cumulative fault indication (about presence of short or open field circuit for any DO channel).

LED fault signaling (for both case 1 and 2): 2 red LEDs (UV and OV of supply 1); 2 red LEDs (UV and OV of supply 2); a cumulative fault red LED.

Relay fault signaling (one for each case 1 or 2): a voltage free NE SPDT - 1 Form C relay contacts (de-energized in fault condition), with the following characteristics:

Contact material: AgCdO.

Contact rating: 2 A 36 Vac 72 VA, 2 A 48 Vdc 80 W (resistive load).

Mechanical / Electrical life: 30 * 10⁶ / 1 * 10⁵ operation, typical.

Coil status LED indication: yellow color, turn on when coil is energized.

Connection: by polarized plug-in disconnect screw terminal blocks to accommodate terminations up to 2.5 mm².

I/O card interface:

Connection: two 25 poles SUB-D male connectors (require female mating connectors).

HART Multiplexing:

Connection: 34 poles male connector (requires female mating connector).

Environmental conditions:

Operating: temperature limits – 40 to + 70 °C, relative humidity max 90 % non condensing, up to 35 °C.

Storage: temperature limits – 45 to + 80 °C.

Mounting:


Hardware included for mounting on wall and single DIN rail.

Weight: about 220 g (excluding modules and mounting options).

Location: Safe Area / Ordinary locations.

Dimensions: Width 147 mm, Depth 176 mm, Height 125 mm.

Image:



Алматы (7273)495-231
Ангарск (3955)42-70-56
Архангельск (8182)63-90-72
Астрахань (8512)99-46-04
Барнаул (3852)73-04-42
Белгород (4735)40-23-142
Благовещенск (4162)35-142-07
Брянск (4232)59-03-52
Владивосток (423)249-42-31
Владикавказ (8672)42-90-42
Владимир (4935) 49-43-18
Волгоград (844)278-03-42
Вологда (8172)26-41-59
Воронеж (473)204-51-73
Екатеринбург (343)384-55-142

Ижевск (3412)26-03-58
Иваново (4932)77-34-06
Иркутск (395)279-98-46
Казань (843)206-01-42
Калининград (4012)72-03-81
Калуга (4242)92-23-67
Кемерово (3842)65-04-62
Киров (8332)68-02-04
Коломна (4966)23-41-49
Кострома (4942)77-07-42
Краснодар (861)203-40-90
Красноярск (391)204-63-61
Курск (4712)77-13-04
Курган (4352)50-90-47
Липецк (4742)52-20-81

Киргизия (996)312-96-26-47

Магнитогорск (4219)55-03-13
Москва (495)268-04-70
Мурманск (8152)59-142-93
Набережные Челны (8552)20-53-41
Нижний Новгород (831)429-08-12
Новокузнецк (3843)20-46-81
Новосибирск (383)357-86-73
Ноябрьск (3496)41-32-12
Ноябрьск (3496)41-32-12
Омск (3812)21-46-40
Орел (4262)44-53-42
Оренбург (4232)37-68-04
Пенза (8412)35-31-16
Петрозаводск (8142)55-98-37
Псков (8112)59-10-37

Россия (495)268-04-70

Пермь (342)205-81-47
Ростов-на-Дону (863)308-18-15
Рязань (4912)46-61-142
Самара (846)206-03-16
Саранск (8342)35-96-24
Санкт-Петербург (812)309-46-40
Саратов (845)249-38-78
Севастополь (8692)35-31-93
Симферополь (3652)67-13-56
Смоленск (4212)29-41-42
Сочи (862)242-72-31
Ставрополь (8652)20-65-13
Сыктывкар (8212)42-95-17
Сургут (3462)77-98-42
Тамбов (4752)50-40-97

Казахстан (772)734-952-31

Тверь (4352)63-31-42
Тольятти (8435)63-91-07
Томск (3835)98-41-53
Тула (4272)33-79-87
Тюмень (3452)66-21-18
Улан-Удэ (3012)59-97-51
Ульяновск (8435)24-23-59
Уфа (347)359-42-12
Хабаровск (4212)92-98-04
Чебоксары (8435)42-53-07
Челябинск (421)202-03-61
Череповец (8202)49-02-142
Чита (3035)38-34-83
Якутск (4112)23-90-97
Ярославль (4422)69-52-93